



Product Code: 1017 T (Self Adhesive Vinyl)

Specification	Description		
PVC (without protective paper and adhesive)	Type	Calendered Monomeric PVC film	
	Thickness	100 ± 10um	
	Color Code	Clear (Transparent)	
	Dimensional Stability	« 0.6%	
	Tensile Strength	ISO 1184	≥ 20 Mpa (MD)
		ISO 1184	≥ 18 Mpa (CD)
Elongation	ISO 1184	≥ 130% (MD)	
	ISO 1184	≥ 130% (CD)	
Adhesive	Type	Clear Solvent Polyacrylate, Permanent	
	Thickness	25 ± 2 g / m ²	
	Application Temperature	15°C ~ 40°C	
	Initial Adhesive Stainless Steel	FINAT FTM-1 > 320 N/m	
	Ultimate Adhesive Stainless Steel	FINAT FTM-1 > 400 N/m	
Release Liner	Type	Single Side PE Coated Paper	
	Weight	168g ± 5g/m ²	
	Release Force	0.1 ~ 0.6 N /4cm	
Shelf Life	12 months under ordinary condition at temperature of 22°C and relative humidity of 50 - 55%		
Application	For short and medium-term outdoor application such as markings, vehicle graphics, signage display and decorations. Indoor exposure is almost unlimited.		

Warranty and Limitation

The products are manufactured with high quality raw materials and advanced technology & equipment, guaranteed by serious and scientific quality control system. All products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the product specification.

Should there is any products defects caused by manufacture, compensation will be limited within certain product price.

Date above are updated results and conclusions of test and is subject to change without prior notice. Soluciones is not responsible for all the performance of this material for a given application. The users of materials should perform their own testing to determine the suitability of the material for the intended use.